



## **Van cửa đồng**

**Giá bán: Liên hệ**

**Suitable Applications:**

Water, Oil, Gas

**Material:**

Brass Body

PTFE Stem Packing

Cast Iron Hand Wheel

**Features:**

Full opening wedge to give reduced friction for uninterrupted flow

Screwed BSP to BS21 taper

Pressure rating shown on valve body

**Technical Data****Pressure:**

Up to 12.5 BAR

**Temperature range:**

-20°C – 120°C

Description	Material
Bonnet	Brass
Wedge	Brass
Gland Nut	Brass
Stem	Brass
Stem Packaging	PTFE
Hand Wheel	Cast Iron

**Sản phẩm khác**



—

## [AWWA/ANSI 250Psi Non-Rising Stem Resilient Seated Gate Valve, Mechanical connection](#)

[Xem thêm AWWA/ANSI 250Psi Non-Rising Stem Resilient Seated Gate Valve, Mechanical connection](#)



—

## [AWWA/ANSI 250Psi Non-Rising Stem Resilient Seated Gate Valve, Flanged connection](#)

[Xem thêm AWWA/ANSI 250Psi Non-Rising Stem Resilient Seated Gate Valve, Flanged connection](#)



—

## [Van cửa ti nổi cánh cao su](#)

[Xem thêm Van cửa ti nổi cánh cao su](#)



—

## [Van cửa ti chìm cánh cao su](#)

[Xem thêm Van cửa ti chìm cánh cao su](#)



—

## [Van cửa ren inox](#)

[Xem thêm Van cửa ren inox](#)



—

## [Van cửa mặt bích ty chìm](#)

[Xem thêm Van cửa mặt bích ty chìm](#)