



## Sleeved Plug Valve

Giá bán: **Liên hệ**

No. P11F

- \* Size Range: 1" ~ 12"
- \* Standard Port
- \* ISO-5211 Actuator Mounting Pad
- \* Flange: ANSI B16.5 Class 150/300/600
- \* Anti-static Device
- \* Fire Safe Design
- \* TFM Sleeve for automatic actuation
- \* Option: Locking Device

## **Description**

### ***FEATURES***

- . \* For Application of Isolation
- . \* PTFE/TFM Sleeve
- . \* Locking Device available
- \* Anti-static Device
- \* Pneumatic Actuator, Limit Switch, Solenoid Valve, Air Filter Regulator, etc.
- . \* Fire Safe Design optional

### ***APPLICABLES CLASS 150/300/600 STANDARDS***

- . \* Valve Design: API599
- . \* Face to Face: ANSI B16.10
- . \* Flanged Ends: ANSI B16.5
- . \* Buttwelding Ends: ANSI B16.25
- . \* Size Range: 1/2"~12"

### ***TEST PRESSURE***

- \* According to API598, API6D

**Sản phẩm khác**



—

[Van bi 3pc có tán inox nổi ren](#)

[Xem thêm Van bi 3pc có tán inox nổi ren](#)



—

[Van bi 3pc inox nổi ren](#)

[Xem thêm Van bi 3pc inox nổi ren](#)



—

[Van bi 3pc inox nối ren tay gạt](#)

[Xem thêm Van bi 3pc inox nối ren tay gạt](#)



—

[Van bi 3 ngã inox nối ren kiểu L hoặc T](#)

[Xem thêm Van bi 3 ngã inox nối ren kiểu L hoặc T](#)



—

[Van bi 3 ngã inox nối ren đóng mở điện On/Off -L kiểu T](#)

[Xem thêm Van bi 3 ngã inox nối ren đóng mở điện On/Off -L kiểu T](#)



—

[Van bi 2pc nối bích tay gạt jis10k pn16](#)

[Xem thêm Van bi 2pc nối bích tay gạt jis10k pn16](#)