



Van bi đồng italia

Giá bán: Liên hệ

No. P11F

- * Size Range: 1" ~ 12"
- * Standard Port
- * ISO-5211 Actuator Mounting Pad
- * Flange: ANSI B16.5 Class 150/300/600
- * Anti-static Device
- * Fire Safe Design
- * TFM Sleeve for automatic actuation
- * Option: Locking Device

Description

FEATURES

- . * For Application of Isolation
- . * PTFE/TFM Sleeve
- . * Locking Device available
- * Anti-static Device
- * Pneumatic Actuator, Limit Switch, Solenoid Valve, Air Filter Regulator, etc.
- . * Fire Safe Design optional

APPLICABLES CLASS 150/300/600 STANDARDS

- . * Valve Design: API599
- . * Face to Face: ANSI B16.10
- . * Flanged Ends: ANSI B16.5
- . * Buttwelding Ends: ANSI B16.25
- . * Size Range: 1/2"~12"

TEST PRESSURE

- * According to API598, API6D

Sản phẩm khác



—

[Van bi 3pc có tán inox nổi ren](#)

[Xem thêm Van bi 3pc có tán inox nổi ren](#)



—

[Van bi 3pc inox nổi ren](#)

[Xem thêm Van bi 3pc inox nổi ren](#)



—

[Van bi 3pc inox nối ren tay gạt](#)

[Xem thêm Van bi 3pc inox nối ren tay gạt](#)



—

[Van bi 3 ngã inox nối ren kiểu L hoặc T](#)

[Xem thêm Van bi 3 ngã inox nối ren kiểu L hoặc T](#)



—

[Van bi 3 ngã inox nối ren đóng mở điện On/Off -L kiểu T](#)

[Xem thêm Van bi 3 ngã inox nối ren đóng mở điện On/Off -L kiểu T](#)



—

[Van bi 2pc nối bích tay gạt jis10k pn16](#)

[Xem thêm Van bi 2pc nối bích tay gạt jis10k pn16](#)