



Van cầu A182-F316 FLGD-FF Cl.150

Giá bán: **Liên hệ**

Size Range:	DN15 - DN600 / 1/2" - 24"
Design Standards:	MSS-SP80 / BS5154/BS1873 /ASME B16.34
Pressure Ratings:	Class 150LB, Class 300LB,CLASS600LB Class900,class1500, PN10~PN250
End Connections:	Flanged ASME B16.5, EN1092-1 (Flat Face FF or Raised Face flange (RF), RING TYPE JOINT FLANGE(RTJ))
Face to Face:	ASME B16.10, ASME B16.47, EN558-1
Globe valve Type:	Through way type, Y type Globe valve, and Angle Type globe valve, OS&Y, Rising Stem.
DISC:	Plug type disc, regulating disc(throttling disc), regular disc.
Seat:	Integral Seat, Optional Extras Renewable Seats 2"/ DN50 and above
Operated type:	Hand wheel, Gear Operated, Pneumatic Operated, Electric Operated, Impact Hand wheel Operated
Pressure Testing:	API 598 or BS EN 12266-1:2003/DIN3230
Optional Extras:	Locking Devices Open and Close Indicator Bare stem with ISO5210 top mounting pad for actuator etc.

Stainless Steel Globe valves : A351 CF8(F304),CF8M(F316),CF3(F304L),CF3M(F316L),CF8C(F347),F321,F321H,CK20 **Alloy Steel Globe valves:** Monel 400, monel k500, alloy20,904L,CN7M, Inconel, Hastelloy® B&C **Duplex Stainless Steel Globe valves:** A351 CN7M(B473), CD4MCu(F50),CK3MCuN(F44),CG8M,A890-1A,4A,5A,6A, A182 F44,F50,F51,F53,F310 **Bronze Globe valves, Nickel aluminum bronze(NAB) Globe valves, Gunmeta Globe valves:** B148 C95500,C95800,C95400,B62, C83600,B61,B62 C92200, B150 C63200 **DIN Stainless Stee Globe valves:** 1.4408, 1.4308

Sản phẩm khác



—

[Van cổng inox 304 nối hàn](#)

[Xem thêm Van cổng inox 304 nối hàn](#)



—

[Van cửa inox 304 nối hàn A182](#)

[Xem thêm Van cửa inox 304 nối hàn A182](#)



—

[Van cầu hơi inox a182](#)

[Xem thêm Van cầu hơi inox a182](#)



—

[Van cổng hàn lồng A105](#)

[Xem thêm Van cổng hàn lồng A105](#)



—

[Van hồi áp lực inox 304 nối hàn a105](#)

[Xem thêm Van hồi áp lực inox 304 nối hàn a105](#)



—

[Van cổng Mặt bích RF, A351-CF8M Class150](#)

[Xem thêm Van cổng Mặt bích RF, A351-CF8M Class150](#)

