



Van cửa đồng

Giá bán: **Liên hệ**

Suitable Applications:

Water, Oil, Gas

Material:

Brass Body

PTFE Stem Packing

Cast Iron Hand Wheel

Features:

Full opening wedge to give reduced friction for uninterrupted flow

Screwed BSP to BS21 taper

Pressure rating shown on valve body

Technical Data**Pressure:**

Up to 12.5 BAR

Temperature range:

-20°C – 120°C

Description	Material
Bonnet	Brass
Wedge	Brass
Gland Nut	Brass
Stem	Brass
Stem Packaging	PTFE
Hand Wheel	Cast Iron

Sản phẩm khác



—

[AWWA/ANSI 250Psi Non-Rising Stem Resilient Seated Gate Valve, Mechanical connection](#)

[Xem thêm AWWA/ANSI 250Psi Non-Rising Stem Resilient Seated Gate Valve, Mechanical connection](#)



—

[AWWA/ANSI 250Psi Non-Rising Stem Resilient Seated Gate Valve, Flanged connection](#)

[Xem thêm AWWA/ANSI 250Psi Non-Rising Stem Resilient Seated Gate Valve, Flanged connection](#)



—

[Van cửa ti nổi cánh cao su](#)

[Xem thêm Van cửa ti nổi cánh cao su](#)



—

[Van cửa ti chìm cánh cao su](#)

[Xem thêm Van cửa ti chìm cánh cao su](#)



—

[Van cửa ren inox](#)

[Xem thêm Van cửa ren inox](#)



—

[Van cửa mặt bích ty chìm](#)

[Xem thêm Van cửa mặt bích ty chìm](#)