



Van điện từ hơi 2L400-15-Round-Star

CÔNG TY TNHH TM DV XNK VAN PHÚ QUANG xin gửi tới quý khách hàng sản phẩm van điện từ sử dụng cho hơi 2L 400 - 15 Hiệu Round Star. Van điện từ 2L 400 - 15 là dòng van 2/2 thân vật liệu bằng đồng. Kiểu van thường đóng (NC). Hoạt động đóng mở trực tiếp, nhiệt độ - 50C đến 1800C, áp lực 0,5 bar đến 16 bar, kết nối ren sử dụng cho hơi nhiệt rất tốt.

VAN ĐIỆN TỬ HƠI 2L 400 - 20 ROUND STAR

* Van điện tử series 2L có các model sau:

2L 160 - 10

2L 160 - 15

2L 200 - 20

2L 250 - 25

2L 350 - 35

2L 400 - 40

* Van điện tử series 2L - Thông số kỹ thuật:

2L-series 2-way piston(NC) steam solenoid valve 3/8"□□□




2L-15J

2L-25

working medium: steam, oil (viscosity ≤ 20cst)
 medium temperature: -5 ~ 180°C
 working pressure: 0.5 ~ 16bar
 working type: pilot operated, NC
 valve body material: brass SS304
 sealing material: PTFE
 interface: G thread, NPT thread
 working voltage: AC220V/240V AC110V 50/60Hz 90VA
 DC24V/12V 30W/15W IP4 H degree
 option: R, thread

order code



2L-series solenoid valve specification table

2L-series solenoid valve drawing

Model	DN (mm)	Interface (mm)	Working medium	Temperature	Working voltage	Weight (kg)
2L-10	10	1/8"	0.5-16	0.5-180	AC220V/240V/110V DC24V/12V	0.3
2L-15	15	1/4"	0.5-16	0.5-180	AC220V/240V/110V DC24V/12V	0.3
2L-20	20	1/2"	0.5-16	0.5-180	AC220V/240V/110V DC24V/12V	0.3
2L-25	25	3/8"	0.5-16	0.5-180	AC220V/240V/110V DC24V/12V	0.3
2L-35	35	1/2"	0.5-16	0.5-180	AC220V/240V/110V DC24V/12V	0.3
2L-40	40	3/4"	0.5-16	0.5-180	AC220V/240V/110V DC24V/12V	0.3



2L-15J

2L-25

Sản phẩm khác



—

[Van điện từ đồng](#)

[Xem thêm Van điện từ đồng](#)



—

[Van điện từ 09](#)

[Xem thêm Van điện từ 09](#)



—

[Flange solenoid valve](#)

[Xem thêm Flange solenoid valve](#)



—

[Van điện từ hơi 180](#)

[Xem thêm Van điện từ hơi 180](#)



—

[Van điện từ thường mở](#)

[Xem thêm Van điện từ thường mở](#)



—

[Van điện từ inox 304](#)

[Xem thêm Van điện từ inox 304](#)