



; (function(\$){ \$(document).ready(function(){ \$("#owl-slider-2383").owlCarousel({ items: 4, lazyLoad:

```
true, navigation: true, pagination: false, itemsDesktop: [1199, 3], itemsDesktopSmall: [979, 2],
itemsTablet: [768, 4], itemsMobile: [479, 3], }); $("#owl-slider-2383 img").click(function() { var imgMain
= $(".imageRoot"), a_imgMain = $(".link-imageRoot"), src = $(this).attr("data-href"), srcFull =
$(this).attr("data-full"); imgMain.attr({ 'src': src, 'data-full': srcFull }); a_imgMain.attr("href", srcFull); });
}); }(jQuery));
```

YT-1000R

Description

The Electro-Pneumatic Positioner YT-1000R is used for operation of pneumatic rotary valve actuators by means of electrical controller or control system with an analog output signal of DC 4 to 20mA or split ranges.

- Simple zero and span adjustment
- No resonance between 5-200Hz
- Auto/Manual switch
- RA v.s. DA action and 1/2 split range setting by simple adjustment.
- Internal feedback signal is available as an option (weather proof only)

Specification

Item · Type	Single	Double
Input Signal	4-20mA DC	
Impedance	250 ± 15 Ω	
Supply Pressure	0.14~0.7MPa(1.4~7 bar)	
Stroke	0 ~ 90°	
Air Connection	PT(NPT,G)1/4	
Gauge Connection	PT(NPT) 1/8	
Conduit	G(PF,NPT)1/2, M20	
Explosion Protection Type	ATEX (II 2 G)Ex dmb IIB T5 IECEX (II 2 G)EEx md IIB T5 KCs Ex dmb IIB T5/Ex d IIC T5 IP66/Ex ia IIB T6 Gb TS Ex db mb IIB T5 Gb X CSA (Class I, Zone 1)Ex dm IIB T5 FM XP-S/1/CD/T5 Ta=60□; DIP/II, IIV/1/EFG/T5 Ta=60□; Type 4X NEPSI Ex dmb IIC T6 Gb TIIS Ex dmb IIB T5	
Ingress Protection	IP66	
Operating Temp	Operating	-20°C~70°C(-4~158°F)
	Explosion	-20°C~60°C(-4~140°F)
Linearity	± 1% F.S.	± 2% F.S.
Hysteresis	± 1% F.S.	
Sensitivity	± 0.2% F.S.	± 0.5% F.S.
Repeatability	± 0.5% F.S.	
Air Consumption	2.5LPM (sup=0.14MPa)	
Flow Capacity	80LPM (sup=0.14MPa)	
Material	Aluminum Diecasting	
Weight	2.8kg (6.2 lb)	

Model	Acting Type	Explosion Protection	Lever Type	Orifice Type	Conduit - Air Connection	Operating Temp*2	Option1	Option2*2
YT-1000R	S Single	N Non-Explosion	1 M6 × 34L	1 φ 1	1 G1/2 - PT1/4	S -20°C ~ 60°C	0 NONE (St'd)	0 NONE
	D Double	M ATEX, IECEX, TS, KCs	2 M6 × 63L	2 φ 2	2 G1/2 - NPT1/4	H -20°C ~ 120°C	1 Dome Cover	1 + SPTM(Internal)
		A CSA, FM	3 M8 × 34L	3 None	3 G1/2 - G1/4	L -40°C ~ 70°C		2 + SPTM(External)
		C KCs, NEPSI	4 M8 × 63L		4 M20 - NPT1/4 *1			3 + L/S(Internal)
		I KCs	5 NAMUR		5 NPT1/2 - NPT1/4			4 + L/S(External)
		X TIIS						5 + SPTM + L/S(Internal)
							6 + SPTM + L/S(External)	

*1 M20 adapter is attached to conduit entry
*2 With high-low temp and/or internal external SPTM, L/S option, positioner must be non-explosion type.

Sản phẩm khác



—

[YT-1050](#)

[Xem thêm YT-1050](#)



—

[YT-1000L](#)

[Xem thêm YT-1000L](#)

