



Manual drain type



Auto drain type

**YT-220**

## Description

Air filter regulator suitably reduce plant's main air supply pressure and supplies to valve positioner(s) or control device(s).

- Maintain stable outlet pressure
- Light weight and compact size
- 5 micron filter
- Relief function – discharge pressure if outer pressure is higher than set pressure

## Specification

Item · Type	YT-200	YT-220	YT-205	YT-225
Max. Supply Pressure	1.7MPa (17 bar)			
Max. Output Pressure	0.42MPa (A Type) , 0.84MPa (B Type)			
Air Connection	PT (NPT) 1/4	PT (NPT) 1/2	NPT 1/4	NPT 1/2
Gauge Connection	PT (NPT) 1/4	PT (NPT) 1/4	NPT 1/4	NPT 1/4
Operating Temp	-20~70°C (-4~158°F) (Standard type)			
Min. Filtering Size	5 micron			
Material	Aluminum Diecasting		Stainless Steel 316	
Weight	0.6kg (1.7lb)	0.86kg (1.89lb)	1.4kg (3.0lb)	2.1kg(4.6lb)

Model	Adjustable Range	Connection Type *1	Gauge	Operating Temp	Option
YT-200	<b>A</b> 0~0.42MPa	<b>P</b> PT	<b>0</b> NONE	<b>1</b> -20~70°C	<b>0</b> Manual drain
YT-205	<b>B</b> 0~0.84MPa	<b>N</b> NPT	<b>1</b> 0~0.4MPa	<b>2</b> -20~120°C *2	<b>1</b> Auto drain
YT-220			<b>2</b> 0~1.0MPa	<b>3</b> -40~70°C *2	
YT-225					

\*1 YT-205, YT-225 is available for NPT connection type ONLY

\*2 Manual drain only

## Sản phẩm khác



—

[YT-205](#)

[Xem thêm YT-205](#)



—

[YT-200](#)

[Xem thêm YT-200](#)