



```
;(function($){$(document).ready(function(){$("#owl-slider-2379").owlCarousel({items:4, lazyLoad:true, navigation:true, pagination:false, itemsDesktop:[1199,3], itemsDesktopSmall:[979,2], itemsTablet:[768,4], itemsMobile:[479,3]});$("#owl-slider-2379 img").click(function(){var imgMain=$(".imageRoot"), a_imgMain=$(".link-imageRoot"), src=$(this).attr("data-href"), srcFull=$(this).attr("data-full");imgMain.attr({'src':src, 'data-full':srcFull});a_imgMain.attr("href", srcFull)});})(jQuery);
```

YT-3300

YT-3300 Smart Valve Positioner accurately controls valve stroke, according to input signal of 4~20mA being delivered from controller.

Description

YT-3300 Smart Valve Positioner accurately controls valve stroke, according to input signal of 4~20mA being delivered from controller.

- Auto calibration
- Auto/Manual switch
- HART communication
- LCD display
- PID control
- 4 buttons for local control
- Feedback signal
- Limit switch

Specification

Item · Type		YT-3300	YT-3350
Input Signal		4~20mA DC	
Supply Pressure		0.14~0.7MPa(1.4~7 bar)	
Stroke	Linear Type	10~150mm	
	Rotary Type	0 ~ 90°	
Impedance		Max.500Ω @ 20mA DC	
Air Connection		PT(NPT,G)1/4	NPT 1/4
Gauge Connection		PT(NPT)1/8	NPT 1/8
Conduit		G(PF,NPT)1/2,M20	G(PF)1/2
Operating Temp	Standard Type.	-30°C ~ 85°C (-22~185° F)	
	Low Temp. Type.	-40°C ~ 85°C (-40~185° F)	
LCD Operating Temp.		-30°C ~ 85°C (-22~185° F)	
Ambient Temp. of Explosion Proof		-40~60°C(T5) / -40~40°C(T6)	
Linearity		±0.5% F.S.	
Hysteresis		±0.5% F.S.	
Sensitivity		±0.2% F.S.	
Repeatability		±0.3% F.S.	
Air Consumption		Below 2LPM (sup=0.14MPa)	
Flow Capacity		70LPM (sup=0.14MPa)	
Output Characteristics		Linear, EQ%, Quick Open user set (16 Point)	
Material		Aluminum Diecasting	Stainless Steel 316
Ingress Protection		IP66	
Explosion Protection Type		ATEX, IECEx Ex ia IIC T5/T6 Gb, EX iaD IIIC T100°C/T85°C Db IP66 NEPSI Ex ia IIC T5/ T6 KCs Ex ia IIC T5/T6, EX iaD IIIC T100°C/T85°C CSA Pending FM Class I, Div 1, Groups ABCD Class I, Zone 0 AEx ia IIC Class II/III, Div 1, Groups EFG Class I, II, III, Div 2, Groups ABCDEFG NEMA Type 4 IP66 AMBENT TEMP: -40°C ~ 60°C (T5) / -40°C ~ 40°C (T6)	
Communication(Optional)		HART(ver.7)	
L/S	Mechanical Type(Omron)	AC 125V, 3A	DC 30V, 2A
Rating	Proximity Type(P&F)	DC 8.2V 8.2mA	
Weight		2kg(4.4lb)	5.1kg(11.2lb)

Sản phẩm khác



—

[YT-3303](#)

[Xem thêm YT-3303](#)



—

[YT-3350](#)

[Xem thêm YT-3350](#)

